

Printing date 23.11.2012 Version number 7 Revision: 23.11.2012

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Hilti HIT-HY150
- · Container size 330 ml, 500 ml, 1400 ml
- · Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use Building and construction work
- · Application of the substance / the preparation Adhesive mortar for anchor fastenings in concrete
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

143 441, Moscow

69th km of Moscow Ring Road, Building 3

Business Park Company "Greenwood"

JSC "Hilti Distribution Ltd."

Mailing address:

Moscow 125047 p / o 117 Phone: A single toll-free number

8 (800) 700 52 52 Fax: 8 (800) 700 52 53

· Informing department:

anchor.hse@hilti.com

see section 16

· Emergency telephone number:

Schweizerisches Toxikologisches Informationszentrum - 24 h Service

Tel.: 0041 / 44 251 51 51 (international)

JSC "Hilti Distribution Ltd." Phone: 8 (800) 700 52 52 Fax: 8 (800) 700 52 53

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Sensitising

R43: May cause sensitisation by skin contact.



O; Oxidising

R7: May cause fire.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

· Label elements

· Labelling according to EU guidelines:

The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (GefStoffV)

· Code letter and hazard designation of product:





Xi Irritant O Oxidising

· Hazard-determining components of labelling:

methacrylic acid, monoester with propane-1,2-diol dibenzoyl peroxide

- · Risk phrases:
- 7 May cause fire.
- 43 May cause sensitisation by skin contact.
- · Safety phrases:
- 3 Keep in a cool place.
- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of water and soap.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

· Special labelling of certain preparations:

Only for trade users / technical specialists

(Contd. on page 2)

(Contd. of page 1)



Safety data sheet according to 1907/2006/EC, Article 31 / ISO 11014

Printing date 23.11.2012 Version number 7 Revision: 23.11.2012

Trade name: Hilti HIT-HY150

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· Additional information:



· Information pertaining to particular dangers for man and environment: A

R 43 May cause sensitisation by skin contact

Information pertaining to particular dangers for man and environment: B

R 43 May cause sensitisation by skin contact

R 7 May cause fire

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

2-Component-foilpack, contains:

Component A: Urethane methacrylate resin, inorganic filler

Component B: Dibenzoyl peroxide, phlegmatized

Mixture of the substances listed below with harmless additions.

· Dangerous components:		
27813-02-1	methacrylic acid, monoester with propane-1,2-diol	10-15%
	🗶 Xi R36; 🔀 Xi R43	
	dibenzoyl peroxide	5-10%
	Xi R36; Xi R43;	
	🔗 🅸 Org. Perox. B, H241; 🗘 Eye Irrit. 2, H319; Skin Sens. 1, H317	

· Dangerous components A:		
27813-02-1 methacrylic acid, monoester with propane-1,2-diol	Xi R36; Xi R43	
	(1) Eye Irrit. 2, H319; Skin Sens. 1, H317	

· Dangerous components B:

- · SVHC None
- · Additional information For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After inhalation Take affected persons into the open air and position comfortably
- $\cdot \textbf{After skin contact} \ Instantly \ wash \ with \ water \ and \ soap \ and \ rinse \ thoroughly. \ If \ skin \ irritation \ persist, \ call \ a \ physician.$
- · After eye contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
- · After swallowing

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

- · Information for doctor
- $\cdot \, \textbf{Most important symptoms and effects, both acute and delayed} \, \, \textbf{Allergic reactions} \\$
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents

Water spray, carbon dioxide (CO2), carbon dioxide blanket, foam, or dry powder.

Sand

- · For safety reasons unsuitable extinguishing agents Water with full jet.
- · Special hazards arising from the substance or mixture

Can be released in case of fire

Carbon monoxide (CO)

Carbon dioxide (CO2) Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

(Contd. on page 3)



Version number 7 Revision: 23.11.2012 Printing date 23.11.2012

Trade name: Hilti HIT-HY150

· Advice for firefighters

(Contd. of page 2)

· Protective equipment: In the event of fire, wear self contained breathing apparatus

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

Keep away from ignition sources

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

· Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Do not allow to enter the ground/soil.

Methods and material for containment and cleaning up:

Collect mechanically.

Clean the accident area carefully; suitable cleaners are:

organic solvent

Dispose of contaminated material as waste according to item 13.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

7 Handling and storage

- · Handling
- · Precautions for safe handling

Check the expiry date: see imprint on manifold (month/year). Do not use expired mortar!

The usual precautionary measures should be adhered to general rules for handling chemicals.

Keep away from heat and direct sunlight.

- Information about protection against explosions and fires: Keep ignition sources away Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and containers: Keep in a cool, dry and dark place; 5 °C to 25 °C.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- Storage class

As per VCI (1991) storage classification concept.

11

· Specific end use(s) Adhesive mortar for anchor fastenings in concrete

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

The product has a pasty consistency. Exposure limit values for respirable dusts ar not relevant for this product.

- · Additional information: The lists that were valid during the compilation were used as basis
- · Exposure controls
- · Personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to general rules for handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat, drink or smoke while working.

Wash hands during breaks and at the end of the work.

Take off immediately all contaminated clothing

Keep away from foodstuffs, beverages and food.

· Breathing equipment: Not required.

· Protection of hands:

Protective gloves EN 374 / EN 388

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Avoid direct contact with the chemical/ the product/ the preparation by organizational measures.

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)



Printing date 23.11.2012 Version number 7 Revision: 23.11.2012

Trade name: Hilti HIT-HY150

 $\cdot \ Penetration \ time \ of \ glove \ material$

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Not suitable are gloves made of the following materials:

Natural rubber, NR

Leather gloves

Strong gloves

• Eye protection: Tightly sealed safety glasses.

EN 166 / EN 170

· Body protection: Protective work clothing.

9 Physical and chemical properties

(Contd. of page 3)

· Information on basic physical and chemical properties			
· General Information			
· Appearance:			
Form:	pasty		
Colour:	Grey		
· Odour:	Ester-like		
· Odour threshold:	Not determined		
· pH-value:	Component A: not applicable		
•	Component B: ~ 6		
· Change in condition			
Melting point/Melting range:	Not determined		
Boiling point/Boiling range:	Not determined		
· Flash point:	Component A: > 100 °C (DIN 53213)		
•	Component B: not applicable		
· Inflammability (solid, gaseous)	Not determined		
· Ignition temperature:	Not determined		
· Decomposition temperature:	Component A: not relevant		
•	Component B: SADT 65°C UN test H4		
· Self-inflammability:	Product is not selfigniting.		
· Danger of explosion:	Product is not explosive.		
· Critical values for explosion:			
Lower:	Not determined		
Upper:	Not determined		

Component A: 0,1 hPa (20 °C)

Not miscible or difficult to mix

1,7 g/cm3 (DIN 51757)

~ 70 Pa.s (DIN 53015)

> 20 s (DIN 53211/4)

Component B: ~ 30%

No further relevant information available.

0 %

Not determined

Not determined Not determined

10 Stability and reactivity

- · Reactivity
- · Chemical stability

· Vapour pressure:

· Density at 20°C

Relative density

· Vapour density

Water:

· Viscosity:

· Evaporation rate

dynamic at 23°C:

· Solvent content: Organic solvents:

Other information

Water:

kinematic at 23°C:

· Solubility in / Miscibility with

· Thermal decomposition / conditions to be avoided:

· Partition coefficient (n-octanol/water): Not determined

To avoid thermal decomposition do not overheat.

- No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known

- RF



Printing date 23.11.2012 Version number 7 Revision: 23.11.2012

Trade name: Hilti HIT-HY150

(Contd. of page 4)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritant effect.
- · Sensitization: Sensitization possible by skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · According to recipe contains the following heavy metals and compounds according to EC guideline NO. 76/464 EC: None
- · General notes: The product does not contain organically bounded halogens (AOX-free).
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- $\cdot \ Waste \ treatment \ methods$
- · Recommendation

For disposal, local regulations issued by the authorities must be observed.

After curing, the product can be disposed of with household waste.

Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations.

_				
	· European waste catalogue			
Ī	08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS,			
		VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS		
	08 04 00	04 00 wastes from MFSU of adhesives and sealants (including waterproofing products)		
		08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances		
Ī	20 00 00	20 00 00 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL		
		WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS		
	20 01 00	separately collected fractions (except 15 01)		
	20 01 27*	paint, inks, adhesives and resins containing dangerous substances		

- · Uncleaned packagings:
- $\cdot \ Recommendation:$

Disposal must be made according to official regulations.

Dispose of packaging according to regulations on the disposal of packagings.

Empty packs: May be disposed via the local Green Dot collecting system or EAK waste material code 150102 (plastic packaging materials)

UN-Number		
ADR, IMDG, IATA	Void	
UN proper shipping name		
ADR, IMDG, IATA	Void	
Transport hazard class(es)		
ADR, IMDG, IATA		
Class	Void	
Packing group		
ADR, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Not applicable.	

(Contd. on page 6)



Printing date 23.11.2012 Version number 7 Revision: 23.11.2012

Trade name: Hilti HIT-HY150

	(Contd. of page 5)	
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.		
· Transport/Additional information:	Not dangerous according to the above specifications. available oxygen content < 1 %	
· HS-Code:	3214 10 10: Glaziers' putty, grafting putty, resin cements, caulking compounds and other mastics	

15 Regulatory information

- $\cdot \, Safety, health \, and \, environmental \, regulations/legislation \, specific \, for \, the \, substance \, or \, mixture \,$
- · National regulations
- · Information about limitation of use: Employment restrictions concerning young persons must be observed.
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 None
- · Chemical safety assessment: not required.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H241 Heating may cause a fire or explosion.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

R3 Extreme risk of explosion by shock, friction, fire or other sources of ignition.

R36 Irritating to eyes.

R43 May cause sensitisation by skin contact.

R7 May cause fire.

· Department issuing data specification sheet:

Hilti Entwicklungsgesellschaft mbH

Hiltistrasse 6

D-86916 Kaufering Tel.: +49 8191 906310 Fax: +49 8191 90176310 e-mail: anchor.hse@hilti.com

· Contact: Mechthild Krauter

 \cdot * Data compared to the previous version altered.

RF ·